






























DESCRIPTION	
 Family : DURA LVT	FUSION
 Construction	Hybrid Clic flooring features an engineered stone polymer composite with a direct fusion to a printed film and a durable embossed wear layer, with bevelled edges, superior dimensional stability and acoustic properties.
 Installation	Välinge 5G Floating Acoustic Installation System
 Standard	Class III, Type B, Class C
 Total Thickness	0.236" (6.0 mm)
 Wear Layer	0.020" (0.50 mm)
 Sizes : Planks	12" x 24"
 Packaging : Planks per Box	10
 Coverage : Sq.ft. per Box	19.37
 Weight : Kg per Box	16.54
 Surface Finish	PUR UV Cured Ceramic Bead Protection : No Wax, No Spray Buff, for the life of the product
PERFORMANCE	
 Chemical and Stain Resistance	ASTM F925-13 : Pass
 Abrasion Resistance	ASTM D4060-14 : Scratch Resistance 
 R10 Slip Resistance	ASTM D2047-11 : Meets or exceeds the industry recommendations for flat surfaces / R10
 Static Load Resistance / Residual Indentation	ASTM F970-15 : Pass
 Wheel Castor Resistance	ASTM D4060-14 : Compliant / Suitable for office chairs with castors
 Dimensional Stability	ASTM F2199-14 : Pass
 Thermal Conductivity	Suitable for heated floors max 28°C (82°F)
 Impact Insulation Class	ASTM E989 : 73 IIC
 Sound Transmission Class	ASTM E413 : 67 STC
 Flame Spread and Smoke Development	CAN/ULC-S102.2 / ASTM E648 Class I / ASTM E662 : Compliant
ENVIRONMENTAL	
 Micro-Organism Resistance	ASTM G21-15 : Bacteriostat, no growth
 Indoor Air Quality, VOC Emission	Phthalate Free Compliant with Floor Score Requirements
 Low Emitting Material	EN 71-3 : In Compliance with CDPH/EHLB Standard Method
 Recycling	100% Recyclable
 Plants Certifications	ISO 9002, ISO14001, OHSAS 18001
 Health and Safety	Compliant with CE regulation
 Limited Warranty	Residential : Lifetime Commercial : 10 years