






























DESCRIPTION	
 Family : DURA LVP	<b>FUSION</b>
 Construction	Hybrid Clic flooring features an engineered stone polymer composite with a direct fusion to a printed film and a durable embossed wear layer, with bevelled edges, superior dimensional stability and acoustic properties.
 Installation	DROP LOCK installation system, with the patented UNICLIC Technology. Natural and rustic wood patterns with registered embossed surface.
 Standard	ASTM F1700, Class III, Type B
 Total Thickness	0.217" (5.5 mm)
 Wear Layer	0.020" (0.50 mm)
 Sizes : Planks	7" x 60"
 Packaging : Planks per Box	9
 Coverage : Sq.ft. per Box	26.81
 Weight : Kg per Box	23.2
 Surface Finish	PUR   UV Cured Ceramic Bead Protection : No Wax, No Spray Buff, for the life of the product
PERFORMANCE	
 Chemical and Stain Resistance	ASTM F925-13 : Pass
 Abrasion Resistance	ASTM D4060-14 : Scratch Resistance 
 Slip Resistance	ASTM D2047-11 : Meets or exceeds the industry recommendations for flat surfaces / R10
 Static Load Resistance / Residual Indentation	ASTM F970-15 : Pass
 Wheel Castor Resistance	ASTM D4060-14 : Compliant / Suitable for office chairs with castors
 Dimensional Stability	ASTM F2199-14 : Pass
 Thermal Conductivity	Suitable for heated floors max 28°C (82°F)
 Impact Insulation Class	ASTM E989 : 73 IIC
 Sound Transmission Class	ASTM E413 : 67 STC
 Flame Spread and Smoke Development	CAN/ULC-S102.2 / ASTM E648 Class I / ASTM E662 : Compliant
ENVIRONMENTAL	
 Micro-Organism Resistance	ASTM G21-15 : Bacteriostat, no growth
 Indoor Air Quality, VOC Emission	Phthalate Free Compliant with Floor Score Requirements
 Low Emitting Material	EN 71-3 : In Compliance with CDPH/EHLB Standard Method
 Recycling	100% Recyclable
 Plants Certifications	ISO 9002, ISO14001, OHSAS 18001
 Health and Safety	Compliant with CE regulation
 Limited Warranty	Residential : Lifetime Commercial : 10 years